



Automotive Equipment

C412 I E - C372 I E

EN Electrohydraulic underbody
scissors type lift



4000 3600



Electrohydraulic underbody double scissors type lift



Electrohydraulic underbody scissors type lift, for tyre specialists, car workshops, and body repairers.

Runboards alignment by **MASTER/SLAVE system**.

Runboard available with extensions only.

Configuration for flush installation.

- A** Strong support of cylinder and removable connections on base and runway for simpler maintenance.
- B** Generously sized, self-lubricating sliding blocks.
- C** Runway with pull-out extension.
- D** Adjustment bolts with rubber to cushion the end of the stroke.



TECHNICAL DATA

	C412 I E	C372 I E
Lift capacity	4000 kg	3600 kg
Lifting time	45 s	
Three phase motor	400/230V - 3kW - 3Ph - 50/60Hz	
Single phase motor	230V - 3kW - 1Ph - 50/60Hz	
Max. lifting height	2010 mm	
Lift min. height	290 mm	270 mm

ACCESSOIRES

All models are equipped with:

- Self-lubricating bushings on all rotating parts.
- Set of 4 rubber pads.

STANDARD

- Pair of cross pieces and pads for off-road vehicles
- Kit for pit installations

OPTIONAL* For other optional accessories, refer to separate catalogue

DIMENSIONS

